

PVC ACCESSORIES STANDARDS

		ASTM D2467			ISO 1452-3		
Diametro Nominal		Internal Diameter (mm)	External Diameter (mm)	Min Lace Length(mm)	Internal Diameter (mm)	External Diameter (mm)	Min Lace Length(mm)
(inch.)	(mm)	10,18	10,59	12,70 -	-	-	-
1/8	-	13,61	14,02	15,88 -	-	-	-
1/4	-	17,04	17,45	19,05	16,10	16,30	14,00
3/8	13	21,23	21,54	22,22	20,10	20,30	16,00
1/2	15	26,57	26,87	25,40	25,10	25,30	18,50
3/4	20	33,27	33,65	28,58	32,10	32,30	22,00
1	25	42,04	42,42	31,75	40,10	40,30	26,00
1	32	48,11	48,56	34,93	50,10	50,30	31,00
2	40	60,17	60,63	38,10	63,10	63,30	37,50
2	50	72,85	73,38	44,45	75,10	75,30	43,50
3	65	88,70	89,31	47,63	90,10	90,30	51,00
3	80	101,40	102,10	53,98	-	-	-
4	-	114,10	114,76	57,15	110,10	110,40	61,00
4	100	141,00	141,81	66,68	-	-	-
5	125	168,00	168,83	76,20	160,20	160,50	86,00
6	150	-	-	--	-	-	-
7	-	218,70	219,84	101,60	-	-	-
8	200	-	-	--	-	-	-
9	-	272,67	273,81	127,00	-	-	-
10	250	323,47	324,61	152,40	-	-	-
12	300						

		BS 4346			JIS K 6743		
Diametro Nominal		Internal Diameter (mm)	External Diameter (mm)	Min Lace Length(mm)	Internal Diameter (mm)	External Diameter (mm)	Min Lace Length(mm)
(inch.)	(mm)	-	-	--	-	-	-
(pulq.)	(mm)	-	-	--	-	-	-
1/8	-	16,80	17,30	14,50	17,80	18,40	25,50
1/4	-	21,00	21,50	16,50	21,80	22,40	29,50
3/8	13	26,40	26,90	19,50	25,80	26,40	34,50
1/2	15	33,20	33,70	22,50	31,80	32,50	39,50
3/4	20	41,90	42,40	27,00	37,70	38,60	43,50
1	25	47,90	48,40	30,00	47,70	48,70	54,50
1	32	60,00	60,60	36,00	59,60	60,80	62,50
2	40	75,00	75,50	43,50	75,50	76,60	60,50
2	50	88,60	88,90	50,50	88,50	89,60	63,50
3	65	-	-	--	-	-	-
3	80	113,90	114,30	63,00	113,40	114,70	83,50
4	-	-	-	--	-	-	-
4	100	167,80	168,30	90,00	139,20	140,80	103,50
5	125	-	-	-	165	166,00	131,50
6	150	-	-	-	214,1	217,00	144,50
7	-	-	-	-	-	-	-
8	200	-	-	-	265	267,70	154,50
9	-	-	-	-	316	318,70	174,50
10	250						
12	300						